



TIPPER SPEC  
**7.6M<sup>3</sup>**  
**AGITATOR**  
**BODY**

## **SITRAK 8x4 T5G**

Cab Chassis or 7.6m<sup>3</sup> AGI Turnkey

- ◆ ALLISON 3200P AUTOMATIC
- ◆ HENDRICKSON AIR RIDE
- ◆ WABCO EBS BRAKING
- ◆ HARDOX GENUINE 450
- ◆ REXROTH PUMP & MOTOR
- ◆ PMP IND. GEARBOX
- ◆ PPG 2-PAK TRUCK & MIXER PAINT
- ◆ MAN EXTRA CABIN & MAN 330HP

**CABIN:** MAN Extra Cab with Fold Down Day Bed and an Electric/Hydraulic Cab Lift

**ENGINE:** MAN MC07 @ 330hp (240kW @ 2300 rpm) / TORQUE: 1,250 Nm @ 1,200 – 1,800 rpm

**TRANSMISSION:** Allison 3200P Automatic with Chelsea Hotshift PTO

**GVM:** 31,000kg

**FRONT AXLE & SUSPENSION:** HF7 @ 7,000kg x 2 with Load Share Spring + FUPS

**REAR AXLE & SUSPENSION:** MCY13 @ 18,000kg (2) on 4-Bag Hendrickson Air  
• C/W DCCL – Cross Locks

**BRAKING SYSTEM:** Dual Air Circuit - Disc Brakes + Exhaust Brake, WABCO EBS, ESC, EBL & ASR





# SITRAK 8x4 T5G

MAN Technology in a SINOTRUK Body

## STANDARD MIXERBOWL FEATURES

- ◆ 6 x Cabin Mirrors (4 x Adjustable)
- ◆ Windscreen Sun Visor & Roof Hatch
- ◆ 200L Alloy Fuel Tank & 45L DEF Tank
- ◆ ISRI Leather Air Driver Seat
- ◆ 4 Camera CCTV System
- ◆ Bluetooth & Dash Touch Screen
- ◆ Factory Climate Control Air Conditioning
- ◆ Wabco Air Dryer and Brake Valving
- ◆ Air Operated Steering Wheel Adjustment
- ◆ LH Cornering External Alarm
- ◆ Transmission Forced Neutral
- ◆ Door Park Brake Alarm
- ◆ Seat Belt Alarm
- ◆ Exhaust Brake System
- ◆ Day Time Running Lights
- ◆ Amber Beacon
- ◆ Cabin Fridge

### TURN-KEY AVAILABLE - STANDARD 7.6 M3 BASIC MIXER BOWL FEATURES

Skin	3mm Hardox 450
Fins, Mix (Discharge)	4mm - High Strength, Wear Resistant Steel
Dishead End	8mm High Tensile, Wear and Corrosion Resistant Steel
Trunnion Rollers	Drop In Type 10,000k Rated (Greaseable With Remote Filling Tubes)
Undercoat	2 Pak Epoxy Primer
Painting (Bowl and Frame)	2 Pak Top Coat Polyurethane In PPG
Loading Hopper	3mm Hardox 450
Discharge Hopper	3mm Hardox 450 With Easy Clean Access
Swivel Chute Jack	Hydraulic With Motor And Pump
Gearbox	PMP Industries (Italy) PMB 6.5
Pump	Rexroth A10VGT071EPHW200
Motor	Rexroth A2FMT080
Hoses	Made To GB/T10544 Specifications
Hydraulic Tank	Combination Hydraulic Tank and Cooler With Fan
Water Tank	Pressurised 200 Lt Aluminium With Slump Gun, Meter and Slump Hose
Additives Tank	Pressurised 200 Lt Aluminium (Approx 100Lt)
Wheel Covers	Plastic Drive and Second Steer Guards